


<b>Datum Electronics Limited</b>	<b>Type 310 Load Indicator</b>
	<ul style="list-style-type: none"> <li>• Compatible with Load Cells 0-3.2mV/V</li> <li>• Simple to Calibrate</li> <li>• PC Interface Software</li> <li>• Outputs 4-20mA, 0-5V</li> <li>• Tare</li> <li>• Peak Hold</li> <li>• 10 Load Cell Calibration Memory</li> <li>• Load Cell Supply</li> <li>• Rechargeable NIMH Batteries</li> </ul>
<p>Designed for use with all conventional load cells the indicator provides a 2x 20 Character LCD readout of the load, its units and status. To calibrate the indicator with a load cell is simple either by using the menu or the set-up disk. The set-up disk also provides free windows utilities to log and display load on a PC. The indicator will store calibration settings for up to 10 load cells.</p>	
<b>Display</b>	2x 20 Character LCD
<b>Outputs</b>	RS232
	4-20mA or 0-5Vdc
<b>Peak Hold Time Resolution</b>	<1/100 sec
<b>Load Cell Excitation</b>	5Vdc
<b>Display Resolution</b>	1:10,000
<b>Linearity</b>	1:6000
<b>Operating Temperature</b>	-10 to +40°C
<b>Battery Life</b>	12hrs
<b>Supply Voltage</b>	15Vdc, auto power off 5 min
<b>Battery Charger</b>	110-230ac, 50/60Hz
<b>Dimensions</b>	220mm x 100mm x 35mm
<p style="text-align: center;"><b>Datum Electronics Limited · Park Road · Ryde · Isle of Wight · PO33 2BE · UK</b>  <a href="http://www.datum-electronics.co.uk">www.datum-electronics.co.uk</a> · <a href="mailto:web@datum-electronics.co.uk">web@datum-electronics.co.uk</a></p>	